





Lumenis Smart LIO[™] Advanced Laser Indirect Ophthalmoscope

Lumenis is proud to present the Smart LIO™, its newest high-end Laser Indirect Ophthalmoscope. Smart LIO[™] offers a new standard of comfort and reliability:



headband, providing easily accessible, fully controllable light. In addition, the Smart LIO™ has 4 different light filters and 3 aperture sizes (see back cover).

illumination provides improved retina visibility and allows for longer battery life.

The new Smart LIO[™] is compatible with all Lumenis photocoagulators and multi-application platforms, allowing you to use one LIO for all your retinal care needs:



Smart532[™]: green photocoagulator with SmartPulse[™] sub-threshold technology.





Vision One

Multi-color photocoagulator. Allows you to choose any desired combination of green (532nm), yellow (577nm) or red (659nm) wavelengths, for optimal clinical outcomes.



SLT + YAG + Smart532™.

The comprehensive solution for ophthalmic practice, providing glaucoma, secondary cataract and retinal therapy within a single unified platform.



Illumination Filter Selection



White Light - Clear settings with no filter. Recommended for inspection of a specific pathology and when a brighter light is desired.



Green Filter - Red free filter. Used for examination of fine blood vessels and identification of microaneurysms.



Blue Filter - Cobalt blue filter for fluorescein angiography.



Diffuser - Extra wide beam of diffused light permits a more relaxed technique during more challenging fundus examinations.

Illumination Aperture Sizes



Large - Suitable for routine examinations through fully dilated pupils.

0

Intermediate - Designed to reduce reflections when entering a partially or poorly dilated pupil. Also ideal for closer inspection of particular fundal areas.



Small - Ideal for small, undilated pupils.

Smart LIO[™] Specifications

LIO Headset

Binocular indirect ophthalmoscope	Modified Keeler
Headset dimensions (all dimensions adjustable)	Height: 22 cm (8.7 in) Width: 25 cm (9.8 in) Length: 38 cm (15 in)
Headset weight	800 g (1.75 lb)
Optical fiber length	5 m / 16.4 feet
Ophthalmoscope Technical Specifications	
Illumination intensity	3500 Lux ±500*
Illumination patch sizes	20/40/60 mm ±10%*
Interpupillary adjustment	48 to 76 mm
Power Supply	
Input mains power	100-240 VAC, 700 mA, 50-60 Hz
Power supply rating	12V: 2.5 A (PSU only)
Compatible Lumenis Lasers and Usable Wavelengths (with Appropriate Eye Safety Filters)	
Spectra / Spectra DP	532 nm (green); 630–680 nm (aiming beam)
Smart532	532 nm (green); 635 nm (aiming beam)
Vision One	532 nm (green); 577 nm (yellow); 659 nm (red); 635 nm (aiming beam)

Working Distances

Approximately 28 cm (11 in) Defined as the distance from the center of the LIO laser mirror to the image of the retina.

* Measurements taken at 440 mm from the front surface of the SmartLIO

Lumenis Inc. 1870 South Milestone Drive Salt Lake City, UT 84104 USA Tel +801-656-2300 Fax +801-656-2429

ISO 13485

Eme Lumenis (Germany) GmbH Heinrich-Hertz-Str 3 D-63303 Dreieich-Dreieichenhain GERMANY Tel +49 (0) 6103 8335 0 AMERICAS San Jose, CA, USA Tel +1 408 764 3000 +1 877 586 3647 Fax +1 408 764 3999
 EMEA

 Dreieich Dreieichenhain,

 Germany

 Tel +49 6103 8335 0

 Fax +49 6103 8335 300

 Roma (RM), Italy

 Tel +39 06 90 75 230

 Fax +39 06 90 75 269

 Hertfordshire, UK

 Tel +44 20 8736 4110

 Fax +44 9 8736 4119

JAPAN

Tokyo, Japan Tel +81 3 4431 8300 Fax +81 3 4431 8301 ASIA / PACIFIC

Beijing, China Tel +86 10 5737 6677 Gurgaon, India Tel +91 124 422 07 95 Kowloon, Hong Kong Tel +852 217 428 00 Fax +852 272 251 51



www.lumenis.com/Ophthalmology

Lumenis® Certified Service | USA Toll-free 1-877-LUMENIS (1-877-586-3647) © 2017 All Rights Reserved. The Lumenis Group of Companies. PB-2008215 Rev. A

(F RX ONLY